

DESCRIPTION

A proprietary, all temperature adhesive designed to enhance adhesion of self-adhered membranes. Designed for applications that require rapid setting and strong tack.

USES

For use with AirOutshield™ SA280 and other self-adhered membranes for wall and roof applications. Apply over substrates that are difficult to achieve adequate adhesion to without an adhesive.

PACKAGING

Product Code	Packaging	Weight
PRMAT05	4.5 Gallon US	18 kg (40 lb)

INSTALLATION

Surfaces must be dry, free from oil, grease, and other contaminants and particles.

Apply SRP AT Adhesive to the substrate by brush, roller or airless sprayer. If using roller, it must have heavy nap (i.e. lamb's wool) for optimum application thickness. Application rates will vary from 150 to 250 sq ft per gallon. Can be applied in temperatures as low as -10°C (14°F). For application at temperatures above 5°C (41°F), consider using SRP HP Primer.

First apply to a small test area of the substrate to confirm adequate adhesion. Once adequate adhesion is confirmed, apply only as much adhesive to substrate as can be covered with membrane within 4 hours. If adhesive is left uncovered for more than 4 hours, apply an additional coat.

DRY TIME

Allow adhesive to dry at least 15-35 minutes until tacky before adhering self-adhering membrane.

Tack Time	15-35 Minutes (25C, 60% RH)
Initial Set	60 Minutes (25C, 60% RH)
Set Through	3-4 Hours (25C, 60% RH)

COMPATIBILITY

Compatible with wood, gypsum board, concrete, masonry, metal surfaces, and other typical construction substrates.

PRECAUTIONS & LIMITATIONS

Contains highly flammable solvents.

Do not attempt to apply over XPS, EPS, and Polyisocyanurates.

Apply when ambient temperature is -12°C (10°F) and 40°C (104°F).

Store indoors at room temperature, away from heat, ignition sources, open flames and direct sunlight.

TECHNICAL SERVICE

Contact us at info@SRPAirOut.com or 866 533 0233

Warranty: The information, and in particular, the recommendations relating to the application and end-use of SRP AirOutshield products, are given in good faith based on SRP AirOutshield's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request or can be accessed on the Internet at www.SRPAirOutshield.com.